

CPU Modules

COM Express Modules (x86)

The following **Intel** CPUs are available:

| CPU Type | RAM | Onboard Network |
|--|---------------------------|--------------------|
| Core i7 4th generation 4 x 2,4 / 3.4 GHz; 47 Watt TDP | max. 16 GB DDR3L 1600MT/s | 1 GbE ¹ |
| Core i5 4th generation 2 x 2,9 GHz; 37 Watt TDP | max. 16 GB DDR3L 1600MT/s | 1 GbE ¹ |
| Core i3 4th generation 2 x 2,4 GHz; 37 Watt TDP | max. 16 GB DDR3L 1600MT/s | 1 GbE ¹ |
| Celeron 2 x 2,2 GHz; 37 Watt TDP | max. 16 GB DDR3L 1600MT/s | 1 GbE ¹ |
| Atom 4 x 1,91 GHz; 10 Watt TDP | max. 8 GB DDR3L 1333 MT/s | 1 GbE ¹ |

The following **AMD** CPUs are available:

| CPU Type | RAM | Onboard Network |
|---|-----------------------------------|--------------------|
| Embedded R max. 2,3 Ghz, 35 Watt TDP | max. 16 GB DDR3 1600 MT/s | 1 GbE ¹ |
| Embedded G max. 4 x 2,4 Ghz, 25 Watt TDP | max. 8 GB DDR3L 1600 MT/s onboard | 1 GbE ¹ |

¹ Additionally a 1 GbE or 10 GbE compute network is available on the baseboard as described in [netboard installation](#)

Apalis Modules (ARM)

The following Modules built according to the **Apalis-standard** are available:

| Manufacturer | CPU Type | CPU Name | GPU | RAM | Onboard Network |
|--------------|----------------|---|---------------------------|--------------------------|-----------------|
| Toradex | ARM Cortex-A9 | Nvidia Tegra 3; 4 x 1,3 Ghz; max. 6 W | 520 MHz | max. 2 GB DDR3 1600 MT/s | 1 GbE |
| Christmann | ARM Cortex-A15 | Samsung Exynos 5250; 2 x 1,7 Ghz; max. 20 W | ARM Mali-T604MP4; 533 MHz | 4 GB DDR3 | 2 x 1 GbE |

Last update:
2015/05/12 documentation:cpu_modules https://recswiki.christmann.info/wiki/doku.php?id=documentation:cpu_modules&rev=1431425516
10:11

From:
<https://recswiki.christmann.info/wiki/> - RECS®|Box Wiki

Permanent link:
https://recswiki.christmann.info/wiki/doku.php?id=documentation:cpu_modules&rev=1431425516

Last update: **2015/05/12 10:11**

