

# Software interface

There are several software interfaces available to monitor the status of the RECS®|Box system. These are the Management WebGUI and a REST API providing XML based monitoring and management functionality.

## Management WebGUI

The Management WebGUI is established on every u.RECS unit. Accessible by any known browser on the assigned IP address and the default port 443. The following views are dependent on the device and assembly.

In general these symbols have the following meaning on every page:

	Everything is OK. Also indicated by a green line in a graph.
	Warnung. Something is wrong, but the system is still fully functional. The system has to be checked so the problem doesn't get worse. Indicated by a yellow line in a graph.
	Critical Error. The system must be checked immediately and maybe has to be shut down to prevent hardware damage. indicated by a red line in a graph.

## Management



Fig. 1

## Settings

The screenshot shows the u.RECS Settings interface with several configuration sections:

- Ethernet Port:**
  - Enable Ethernet Port:
  - DHCP Enable:
  - IP Address: 192.168.0.10
  - Netmask: 255.255.255.0
  - Gateway: 192.168.0.1
  - DNS Primary: 192.168.0.1
  - DNS Secondary: 192.168.0.2

Save
- WiFi:**
  - Enable WiFi:
  - SSID: MySSID
  - Passwd: MySecurePassword
  - DHCP Enable:
  - IP Address: 192.168.1.10
  - Netmask: 255.255.255.0
  - Gateway: 192.168.0.1
  - DNS Primary: 192.168.0.1
  - DNS Secondary: 192.168.0.2

Save
- LoRa:**
  - Enable LoRa:
  - Joined LoRa Network: No
  - DevEUI:
  - JoinEUI:
  - AppKey:

Scan the following QR code to get your LoRa settings.

Save
- Fan:**

Speed: 100 %

Save
- Date + Time:**
  - Enable NTP Client:
  - NTP Server 1: TT.WW.IIIIZ. --- : ---
  - NTP Server 2: 1.pool.ntp.org
  - NTP Server 3: 2.pool.ntp.org
  - GMT-12:00 Eastern, Keweenaw

Save
- Admin Password:**

User: admin

Password: New Secure Password

Save
- Firmware:**

Firmware version: 0837bd2-dirty

Fig. 1

# REST API

## Access

The u.RECS Management API is accessible via the IP-Address or the hostname of the u.RECS. The basic URL of the API has the format `https:<ip-address>/REST/<system/baseboard/node>` or `http:<ip-address>/REST/<system/baseboard/node>`.

Accessing the REST API requires HTTP Basic authentication. The password of the admin account can be changed in the Settings page.

## Components

The RECS®|Box Management API makes all hardware components in the cluster available as XML trees in software. The following components are supported by the API:

Attribute	Description
node	A single node
baseboard	Overview about the baseboard that can be equipped with 1 or 2 nodes
system	Overview of the whole system (baseboard + node)
lorawan	Enables communication to LoRaWAN application servers

Many resources also return lists of components. These are named according to the scheme `<component name>List` (e.g. `nodeList`, `rcuList`) and contain the elements of the list.

## Node

Example XML:

```

<nodeList>
    <node maxPowerUsage="26" baseboardPosition="0" architecture="unknown
(SMARC)" baseboardId="RCU_0_BB_1" voltage="5.64"
        actualNodePowerUsage="2.8" actualPowerUsage="2.8" state="0"
        lastPowerState="0" defaultPowerState="0"
        rcuId="RCU_0" health="OK" lastSensorUpdate="1369" id="RCU_0_BB_1_0"
        present="true" bootDevice="0"/>
    <node maxPowerUsage="27" baseboardPosition="0" architecture="ARM + iGPU"
        baseboardId="RCU_0_BB_1" voltage="5.64"
        actualNodePowerUsage="2.8" actualPowerUsage="2.8" state="0"
        lastPowerState="0" defaultPowerState="0"
        rcuId="RCU_0" health="OK" lastSensorUpdate="1369" id="RCU_0_BB_1_1"
        present="false" mpciePresent="false" forceRecovery="false"/>
</nodeList>

```

The following table shows the possible attributes (some are optional) and their meaning:

Attribute	Description	Unit	Data type
id	Unique ID for referencing the component	-	String
actualPowerUsage	Actual power consumption of a node (Node + PEG)	W	Double
actualNodePowerUsage	Actual power consumption of a node (Node only)	W	Double
actualPEGPowerUsage	Actual power consumption of a PEG card	W	Double
maxPowerUsage	Maximum power the node can draw	W	Integer
baseboardId	ID of the baseboard which hosts the node	-	String
baseboardPosition	Position of the node on the baseboard	-	Integer
state	Power state of the node (0=Off, 1=On, 2=Soft-off, 3=Standby, 4=Hibernate)	-	Integer
architecture	Architecture (x86, arm, UNKNOWN)	-	String
health	Health status of the node (OK, Warning, Critical)	-	String
inletTemperature	Temperature of the inlet air	°C	Double
outletTemperature	Temperature of the outlet air	°C	Double
highestTemperature	Highest temperature measured on the node's baseboard	°C	Double
voltage	Supply voltage of the baseboard	V	Double
lastSensorUpdate	Timestamp of the last sensor update	ms	Long
macAddressCompute	MAC address of the NIC connected to the compute network (optional)	-	String
macAddressMgmt	MAC address of the NIC connected to the management network (optional)	-	String

In accordance to the component node the API offers nodeList which returns multiple instances of node.

## Baseboard

Example XML:

```
<baseboard serialNumber="90380CA9D524" rcuPosition="0"
baseboardType="u.RECS" id="RCU_0_BB_1" lastSensorUpdate="358"
    rcuId="RCU_0" inputVoltage="22.93" boardVoltage1V0="1.97"
    boardVoltage1V2="2.05" boardVoltage1V5="2.05"
    boardVoltage1V8="2.05" boardVoltage2V5="2.82" boardVoltage5V0="5.64"
    totalPowerUsage="11.24" usbPowerUsage="2.8"
    mPciePowerUsage="1.64" m2PowerUsage="1.64" ethSwitchPowerUsage="0"
    poePowerUsagePort1="0" poePowerUsagePort2="0"
    regulatorsTemperature="0" ambientTemperature="0" fanSpeed="100"
    systemFan1Rpm="0" systemFan2Rpm="0" loraJoined="false"
    loraJoinEui="0000000000000000" loraDevEui="1234561234561234"
    loraAppKey="01234567890123456789012345678901"
    loraVendorID="FFFF" loraVendorProfileID="0001"
    poeDetectionStatusPort1="0" poeDetectionStatusPort2="0"
    firmwareVersion="0837db2">
```

```
<nodeId>RCU_0_BB_1_0</nodeId>
<nodeId>RCU_0_BB_1_1</nodeId>
</baseboard>
```

The attributes have the following meaning:

Attribute	Description	Unit	Data type
id	Unique ID for referencing the component	-	String
rcuId	Unique ID of the RECS® Box Computing Unit hosting the baseboard	-	String
rcuPosition	Position of the baseboard inside the RECS® Box Computing Unit	-	Integer
infrastructurePower	Power usage of the infrastructure components on the baseboard	W	Double
lastSensorUpdate	Timestamp of the last sensor update	ms	Long
baseboardType	Type of the baseboard (CXP, APLS)	-	String
nodeId	List of IDs of the nodes installed on the baseboard	-	String
temperatures	List of temperatures measured on the backplane	°C	Double

In accordance to the component baseboard the API offers baseboardList which returns multiple instances of baseboard.

## System

Example XML:

```
<system>
  <baseboard serialNumber="90380CA9D524" rcuPosition="0"
  baseboardType="u.RECS" id="RCU_0_BB_1" lastSensorUpdate="1403"
    rcuId="RCU_0" inputVoltage="22.93" boardVoltage1V0="1.97"
    boardVoltage1V2="2.05" boardVoltage1V5="2.05"
    boardVoltage1V8="2.05" boardVoltage2V5="2.82" boardVoltage5V0="5.64"
    totalPowerUsage="11.24" usbPowerUsage="2.8"
    mPciePowerUsage="1.64" m2PowerUsage="1.64" ethSwitchPowerUsage="0"
    poePowerUsagePort1="0" poePowerUsagePort2="0"
    regulatorsTemperature="0" ambientTemperature="0" fanSpeed="100"
    systemFan1Rpm="0" systemFan2Rpm="0" loraJoined="false"
    loraJoinEui="0000000000000000" loraDevEui="1234561234561234"
    loraAppKey="01234567890123456789012345678901"
    loraVendorID="FFFF" loraVendorProfileID="0001"
    poeDetectionStatusPort1="0" poeDetectionStatusPort2="0"
      firmwareVersion="0837db2-dirty">
    <nodeId>RCU_0_BB_1_0</nodeId>
    <nodeId>RCU_0_BB_1_1</nodeId>
  </baseboard>
  <nodeList>
    <node maxPowerUsage="26" baseboardPosition="0" architecture="unknown
(SMARC)" baseboardId="RCU_0_BB_1" voltage="5.64"
      actualNodePowerUsage="2.8" actualPowerUsage="2.8" state="0"
```

```
lastPowerState="0" defaultPowerState="0" rcuId="RCU_0"
    health="OK" lastSensorUpdate="1403" id="RCU_0_BB_1_0" present="true"
bootDevice="0"/>
    <node maxPowerUsage="27" baseboardPosition="0" architecture="ARM + iGPU"
baseboardId="RCU_0_BB_1" voltage="5.64"
        actualNodePowerUsage="2.8" actualPowerUsage="2.8" state="0"
lastPowerState="0" defaultPowerState="0" rcuId="RCU_0"
    health="OK" lastSensorUpdate="1403" id="RCU_0_BB_1_1" present="false"
mpciePresent="false" forceRecovery="false"/>
</nodeList>
</system>
```

## Resources

The resources are split into monitoring resources (for pure information gathering) and management resources (for changing the system configuration or state).

### Monitoring

For monitoring the following resources are available:

Attribute	Description	HTTP Method
/node	Returns a nodeList with all nodes of the system	GET
/baseboard	Returns an overview of the baseboard including the installed nodes	GET
/system	Returns an overview of the baseboard and all nodes	GET

### Management

The management of individual components can be found under the “manage” path of the component.

Attribute	Description	HTTP method	Parameter
/node/{node_id}/manage/power_on	Turns on the node with the given ID and returns updated node XML	POST	
/node/{node_id}/manage/power_off	Turns off the node with the given ID and returns updated node XML	POST	
/node/{node_id}/manage/reset	Resets the node with the given ID and returns updated node XML	POST	

<b>Attribute</b>	<b>Description</b>	<b>HTTP method</b>	<b>Parameter</b>
/node/{node_id}/manage/select_kvm	Switches the KVM port of the RECS® Box Computing Unit containing the node to the node with the given ID and returns updated node XML	PUT	
/rcu/{rcu_id}/manage/set_fans	Sets the overall fan speed of the RCU with the given ID and returns the current status of the RCU	PUT	percent={value}

## LoRaWAN

The LoRaWAN interface allows up and downlink connections to an application server. Packets can be scheduled and collected by interfacing the Management REST API

<b>Attribute</b>	<b>Description</b>	<b>HTTP method</b>
/lorawan/queue	Responds with incoming LoRaWAN packets linked to the API key in the request body XML	POST
/lorawan/queue	Schedules uplink packet to the application server defined in the management interface XML	GET
/lorawan/manage	Manages LoRa PHY settings XML	GET

Example XML queue GET / POST:

```
<lorawan apikey="...">
<packetbody>lora packet content in base64</packetbody>
</lorawan>
```

Example XML manage:

```
<lorawan masterkey="...">
<band>eu</band>
<txpwr>14</txpwr>
<txsf>7</txsf>
<rx2wsf>9</rx2wsf>
</lorawan>
```

In order to remotely manage the RECS power status via LoRaWAN, the Application Server must send the downlink command payload in following format:

```
<l masterkey="">
  <power>1</power>
<l>
```

The master and API keys are managed in the RECS web interface.

## Errors

Information about the success or failure of management requests are returned via HTTP status codes.  
Please have a look at [RFC2616](#) for an overview about the defined HTTP status codes.

From:

<https://recswiki.christmann.info/wiki/> - RECS®|Box Wiki

Permanent link:

[https://recswiki.christmann.info/wiki/doku.php?id=doc\\_urecs:software\\_interface&rev=1697557292](https://recswiki.christmann.info/wiki/doku.php?id=doc_urecs:software_interface&rev=1697557292)

Last update: **2023/10/17 15:41**

